

SunGuard® SuperNeutral

SN 70/35


High on your list for low heat gain

Excellent light transmission is possible without the heat that usually comes with it. SunGuard® SuperNeutral® (SN) 70/35 is a neutral blue glass that offers solar protection while reducing the need for artificial light. Ideal for fully glazed facades and large frame windows, SN 70/35 combines excellent solar protection with outstanding thermal insulation.



Product Information	
Substrate Base Glass/Thickness	Guardian ExtraClear/4-12 mm Guardian UltraClear/4-12 mm
Applications	Facades / Windows / Doors / Curtain Walls / Roofs
Manufacturing options	Annealed / Heat Treated and TPF (Temporary Protective Film) for processing prior to tempering for HT versions / Laminated / Bent
Recommended Coating Positions	Surface 2 (double IGU) Surface 2 (triple IGU)
Maximum Size	<3210x6000mm
Edge Deletion	Yes
Glass type	Double Silver Coated Glass
Glass functions	Solar Control Thermal Insulation
Fabrication options	Must be used in Insulating Glass Units
Appearance	Neutral blue







Published Date: 22-Jul-2022

Double Glazed

Triple Glazed

Visible light			Ultraviolet	Solar Energy						Thermal Properties		
Transmittance	Reflec	tance	General Color Rendering Index (Ra)		Transmittance	Refle	ctance	Absorptance		Shading	U-Value	
Visible (τν %)	pv % out	pv % in		Rendering Index	Trans UV(τuν %)	Solar (te %)	ρe % out	pe % in	Solar(αe %)	Solar Factor(g%)	Coefficient (sc)	Ug W/m²·K
Double Glazed: 6-1	6-4 SunGuard® Supe	rNeutral SN 70/35 or	n Guardian ExtraClea	r #2, Guardian ExtraC	Clear, 90% Argon fill							
70	14	15	94	8	33	42	45	25	35	0.40	1.0	
Double Glazed: 6-1	Double Glazed: 6-16-4 SunGuard® SuperNeutral SN 70/35 on Guardian UltraClear #2, Guardian UltraClear, 90% Argon fill											
71	13	15	95	9	34	49	49	18	35	0.40	1.0	
Triple Glazed: 6-16-	Triple Glazed: 6-16-4-16-4 SunGuard® SuperNeutral SN 70/35 on Guardian ExtraClear #2, Guardian ExtraClear, ClimaGuard® A 1.1 on Guardian ExtraClear #5, 90% Argon fill											
62	16	19	93	5	28	44	40	28	32	0.37	0.5	
Triple Glazed: 6-16-	4-16-4 SunGuard® S	uperNeutral SN 70/3	5 on Guardian UltraC	lear #2, Guardian Ult	raClear, ClimaGuard	® A 1.1 on Guardian	ExtraClear #5, 90% A	rgon fill				
62	16	19	94	5	29	50	42	21	33	0.37	0.5	

The performance values shown are nominal and subject to variations due to manufacturing tolerances. Spectra-photometric values according to EN 410:2011, EN 673:2011 / Metric.

www.guardianglass.com

All trademarks noted are owned by, licensed to or used with permission by Guardian Glass.

©2021 Guardian Glass, LLC

19, rue du Puits Romain L-8070 Bertrange Grande-Duchy de Luxembourg Phone: +352 27 86 32 60 e-mail: information@guardian.com

The products in this publication are sold subject to Guardian's standard terms and conditions of sale and any applicable written warranties (available at www.guardianglass.com or from your local Guardian representative upon request). It is the responsibility of the purchaser to confirm that the products are suitable for their intended application in compliance with the applicable laws and regulations. Please contact your local Guardian representative to obtain any applicable handling and fabrication guides and for the most current product information.