

## ENERGY EFFICIENCY

Thermal Transmission Coefficient

**$U_w$  from 0.9 (W/m<sup>2</sup>K)**

Please consult typology, dimensions and glazing

## ACCOUSTIC INSULATION

Maximum glazing: **55 mm.**

Maximum acoustic insulation: **Rw = 43 dB.**

## CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmosphere agents

Air permeability (UNE-EN 12207:2000):

**Class 4**

Water tightness (UNE-EN 12208:2000):

**Class 9A**

Wind resistance (UNE-EN 12210:2000):

**Class C5**

\*Reference test: 4.0 x 2.4 m. 2 sashes

<b>SECTIONS</b>	Frame 160.6 mm Triple rail 251 mm Sash 70 mm	<b>EXTRUSION ALLOY</b> 6063 T-5
<b>PROFILE THICKNESS</b>	Door 2.0 mm	<b>POLYAMIDE STRIP LENGTH</b> Polyamide 6.6 reinforced with 25% fiberglass: Frame 35 mm Sash 24 mm
<b>MAXIMUM DIMENSIONS</b>	Width (L) = 3,300 mm Height (H) = 3,300 mm	<b>OPENING POSSIBILITIES</b> Sliding 2, 3, 4 and 6 sashes. Optionally monorail (1 sash+1 fixed) Optionally triple rail.
<b>MAXIMUM WEIGHT/SASH</b>	400 Kg	
<b>DRAINAGE</b>	Optionally drainage system and drainage grid made of stainless steel	

Please consult regarding maximum weight and dimensions according to types

## FINISHES

Colour powder coating  
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras  
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

